

## Fitting JSP Filters to the FORCE8 Mask

Please find below a rough and ready explanation of an alternative method to fit JSP filters to the FORCE8 mask.

My dominant hand is my right hand – this will be used to fit and secure the filter. My left hand will be used to support and cradle the mask.

The mask is orientated like so, (in your left hand) with the Red Arrow baseline facing the **web** of the hand. The true Red Arrow is then pointing and facing away from the body.

**Note:** thumb and finger are placed on the harness buckles respectively before cradling them to support the underside of the filter matting surface.



With your right hand, identify the White Arrow on the underside of the filter, just beneath the gasket. Your right hand being the dominant (stronger hand) will be used to orientate one of the filters.

The Red Arrow identified on the mask along with the White Arrow upon the underside of the filter are then aligned together.

Ensure both surfaces (Filter & Mask) are identically flat against one another before applying a little pressure/compression of '3 – 5 seconds' If need be, both hands that are supporting the product can be brought close to the chest to aide compression.

## **MANUFACTURING FOR SAFETY**

JSP Limited, Worsham Mill, Minster Lovell, Oxford, OX29 0TA | Telephone: +441993 824000 | Fax: +441993 824422 sales@jgpsafety.com | www.jgpsafety.com

Registered in England: No. 791380. Carrick House, Lypiatt Road, Cheltenham, Gloucestershire, GL50 2QJ. VAT Number: GB 222 2162 61

Continue the compression method by using both hands (FOR and AGAINST) ensuring the mating surfaces are flat. **Whilst continuing compression** twist the filter in a clockwise direction until the resistance is felt - and then stop.

The WHITE ARROW can be seen situated just above the horizontal line (compass line/East, West) of the exhalation valve clear protective cap.

Note: If you have been unable to locate the white filter arrow to the horizontal line on your first attempt continue the compression and twist action until the white filter arrow is located - as seen in the image below.



Continue the same method when fitting the other filter.

Fitting the filter analogy - *just like a twisting open a prescription pill bottle. Compression is the winner.*

The YOU TUBE links may be of assistance to you:

<https://www.youtube.com/watch?v=HkcBYELutNo>

[https://www.youtube.com/watch?v=Xbrqz4ufL\\_o](https://www.youtube.com/watch?v=Xbrqz4ufL_o)

Daren Metcalf  
Respiratory Manager  
JSP Limited

## MANUFACTURING FOR SAFETY

JSP Limited, Worsham Mill, Minster Lovell, Oxford, OX29 0TA | Telephone: +441993 824000 | Fax: +441993 824422 sales@jpsafety.com | www.jpsafety.com

Registered in England: No. 791380. Carrick House, Lypiatt Road, Cheltenham, Gloucestershire, GL50 2QJ. VAT Number: GB 222 2162 61

